



### Safety Benefits:

VSLs can reduce crashes on freeways up to:

**34%**

for total crashes.<sup>1</sup>

**65%**

for rear-end crashes.<sup>1</sup>

**51%**

for fatal and injury crashes.<sup>1</sup>

**Benefit/Cost Ratios range between<sup>1</sup>**

**9:1 - 40:1**

For more information on this and other FHWA Proven Safety Countermeasures, please visit <https://safety.fhwa.dot.gov/provencountermeasures/> and [https://safety.fhwa.dot.gov/speedmgt/ref\\_mats/](https://safety.fhwa.dot.gov/speedmgt/ref_mats/).

## Variable Speed Limits

Selecting appropriate speed limits on roadways is important in maintaining a safe and efficient transportation network. Speed limits are established with an engineering study based on inputs like traffic volumes, operating speeds, roadway characteristics, and crash history. However, conditions on the roadway are susceptible to change in a short amount of time (e.g., congestion, crashes, weather). Drivers typically determine their operating speeds under normal weather conditions on a straight roadway section with good pavement quality and adequate sight distances. If ideal conditions do not exist and the roadway does not meet the driver's expectations, there is a greater chance that a driver error could result in a crash. Providing variable speeds limits (VSLs) capable of adapting to changing circumstances could reduce crash frequency and severity.

Speed management strategies, including VSLs, are integral to the Safe Speeds element of the Safe System Approach. Because humans are unlikely to survive high-speed crashes, VSLs reduce speeds so that human injury tolerances are accommodated in three ways: improving visibility, providing additional time for drivers to stop, and reducing impact forces.

### Applications

VSLs use prevailing information on the roadway, like traffic speed, volumes, weather, and road surface conditions, to determine appropriate speeds and display them to drivers. This strategy improves safety performance and traffic flow by reducing speed variance (i.e., improving speed harmonization). VSLs may also improve driver expectation by providing information in advance of slowdowns and potential lane closures, which could reduce the probability for secondary crashes. VSLs can mitigate adverse weather conditions or to slow faster-moving traffic as it approaches a queue or bottleneck.

Agencies can implement VSLs for the following applications:



CONGESTION



INCIDENTS



WORK ZONES



INCLEMENT WEATHER

### Considerations

- Particularly effective on urban and rural freeways and high-speed arterials with posted speed limits greater than 40 mph.
- Often implemented as part of Active Traffic Management (ATM) plans or incorporated into existing Road Weather Information Systems.
- When used with ATM, VSLs can mitigate rear-end, sideswipe, and other crashes on high-speed roadways.
- May be implemented as a regulatory and/or an advisory system.
- Can be applied to an entire roadway segment or individual lanes.



Source: WSDOT

<sup>1</sup> Avelar et al. Developing Crash Modification Factors for Variable Speed Limit. FHWA, (2020).