

1200 New Jersey Ave., SE Washington, D.C. 20590

In Reply Refer To: HSST-1/WZ-452

Ben Cohen Bone Safety 6450 Industrial Way Alpharetta, GA 30004 USA

Dear Mr. Cohen:

We received your correspondence of March 22, 2021 requesting issuance of a reimbursement eligibility letter under the Federal-aid highway program for the roadside safety system, device, design, product, or hardware (collectively "device") described below. This letter is assigned Federal Highway Administration (FHWA) control number WZ-452.

# **ELIGIBILITY LETTERS**

The FHWA issues Federal-aid reimbursement eligibility letters for new roadside safety devices that are crash tested in accordance with the industry standard of the American Association of State Highway and Transportation Officials (AASHTO) Manual for Assessing Safety Hardware (MASH).

FHWA, the Department of Transportation, and the United States (government) do not regulate roadside safety devices, crash test facilities, or the manufacturing industry. Issuance of eligibility letters is discretionary and provided only as a service to the states. FHWA may, at its discretion, decline to issue, revise, or rescind an eligibility letter. Eligibility letters are only issued by the FHWA headquarters Office of Safety.

Eligibility letters are issued only as notice to the states that a device is eligible for reimbursement under the Federal-aid highway program. They do not establish approval or certification for any other purpose. Issuance of an eligibility letter is not a prerequisite or requirement for state transportation agencies seeking to use Federal-aid funds for roadside safety devices. State agencies may use a device for which an eligibility letter has not been issued and seek Federal-aid reimbursement.

### FEDERAL-AID REIMBURSEMENT

The request for issuance of this letter certified the device was crash tested in accordance with the industry standard of AASHTO's MASH. This eligibility letter is based on that certification and the material offered in support of its issuance. The device described below is eligible for reimbursement under the Federal-aid highway program.

Name of system: SZ-412

Type of system: Work Zone Sign Stand Test Level: Test Level 3

Testing conducted by: Calspan Corporation

Date of request: March 22, 2021

Information about the device, including material such as the eligibility request, crash test reports, drawings, or images are included in one or more attachment(s) to this letter.

Eligibility letter WZ-452 is inapplicable to devices, optional equipment, alternate materials, or other features that were not crash tested in accordance with AASHTO's MASH.

This letter is issued only for the subject device as crash tested under AASHTO's MASH. Later modification(s) of the device are not eligible for Federal-aid reimbursement under this letter. Notice of later modification(s) should be given to transportation agencies, facility owners, and operators (collectively "agencies").

Agencies should be provided appropriate information about the device's design, installation, maintenance, materials, and mechanical properties.

Issuance of this letter is discretionary, and it may be revised or rescinded at FHWA's discretion. This letter is not a determination of compliance with the Manual on Uniform Traffic Control Devices for Streets and Highways (MUTCD) or ownership of any intellectual property rights.

This eligibility letter is not a determination by the government that a crash involving the subject device will result in any particular outcome. It is limited to only the device's eligibility for Federal-aid reimbursement.

## **INTELLECTUAL PROPERTY**

Issuance of this eligibility letter does not convey property rights of any sort nor any exclusive privilege. This letter is not authorization or consent by the government for the use, manufacture, or sale of any patented or proprietary system, device, design, product, or hardware for which the requester is not the patent owner. Eligibility letters are not an expression of any view, position, or determination by the government as to the validity, scope, or ownership of any intellectual property rights to a specific device. These letters do not grant, impute, suggest, or otherwise establish any ownership, distribution, or licensing rights to the requester. The government expresses no opinion about the intellectual property rights relating to any device for which this or any other eligibility letter is issued.

#### PUBLIC DISCLOSURE

To prevent any misunderstanding, and as discussed above, this eligibility letter is assigned FHWA control number WZ-452. It should only be reproduced in full with its attachment(s). This letter and the material offered by the requester supporting its issuance is public information. All eligibility letters and supporting material are subject to public disclosure under the Freedom

of Information Act (FOIA). Eligibility letters are available to the public at <a href="https://safety.fhwa.dot.gov/roadway">https://safety.fhwa.dot.gov/roadway</a> dept/countermeasures/reduce crash severity/.

If you have any questions please contact Aimee Zhang at Aimee.Zhang@dot.gov.

Sincerely,

Michael S. Griffith

Michael S. Griffith

Director, Office of Safety Technologies

Office of Safety

**Enclosures** 

# Request for Federal Aid Reimbursement Eligibility of Highway Safety Hardware

	Date of Request	March 22, 2021	<ul><li>New</li></ul>	Resubmission
Name: Ben Cohen				
Submitter	Company:	Bone Safety		
h	Address:	: 6450 Industrial Way, Alpharetta, GA 30004		
Su	Country:	/: USA		
		Michael S. Griffith, Director FHWA, Office of Safety Technologies		

I request the following devices be considered eligible for reimbursement under the Federal-aid highway program.

# <u>Device & Testing Criterion</u> – Enter from right to left starting with Test Level

!-!-!

System Type	Submission Type	Device Name / Variant	Testing Criterion	Test Level
'WZ': Crash Worthy Work Zone Traffic Control Devices	<ul><li>Physical Crash Testing</li><li>Engineering Analysis</li></ul>	SZ-412	AASHTO MASH	TL3

By submitting this request for review and evaluation by the Federal Highway Administration, I certify that the product(s) was (were) tested in conformity with the AASHTO Manual for Assessing Safety Hardware and that the evaluation results meet the appropriate evaluation criteria in the MASH.

# Individual or Organization responsible for the product:

Contact Name:	Ben Cohen	Same as Submitter 🛛
Company Name	Bone Safety	Same As Submitter 🖂
Address:	6450 Industrial Way, Alpharetta, GA 30004	Same as Submitter 🖂
Country:	USA	Same as Submitter 🖂

Enter below all disclosures of financial interests as required by the FHWA `Federal-Aid Reimbursement Eligibility Process for Safety Hardware Devices' document.

Bone Safety of Alpharetta, GA and Calspan Corporation share no financial interests between the two organizations. This includes no shared financial interest but not limited to:

- i. Compensation including wages, salaries, commissions, professional fees, or fees for business referrals.
- iii. Research funding or other forms of research support;
- iv. Patents, copyrights, licenses, and other intellectual property interests;
- vi. Business ownership and investment interests;

# PRODUCT DESCRIPTION

New Hardware or Significant Modification	Modification to Existing Hardware		
The Bone Safety SZ-412 work zone safety sign stand attached a roll-up sign at 48" by 48" in size and a bottom height of 12". It is manufactured from steel component parts which have been powder-coated and clear zinc-plated to minimize corrosion. The sign stand is designed using basic nut & bolt construction, so that all component parts may be readily replaced if worn or damaged.			
Legs have both a pull-pin and kick release mechanism for releasing legs. The sign stand measures $6.50^{\circ}$ x $6.50^{\circ}$ x $24^{\circ}$ when folded for storage and have a total weight of 20 lbs. Please reference Appendix C for the corresponding drawing package illustrating the design and component materials, of the test article.			
	CRASH TESTING		
By signature below, the Engineer affiliated with the testing laboratory agrees in support of this submission that all of the critical and relevant crash tests for this device listed above were conducted to meet the MASH test criteria. The Engineer has determined that no other crash tests are necessary to determine the device meets the MASH criteria.			
Engineer Name:	Mark Parisi		
Engineer Signature:	MARK PARK	ned by Mark J. Parisi 4.02 13:10:12 -04'00'	
Address:	4455 Genesee Street, Cheektowaga, NY 14225	Same as Submitter	
Country:	USA	Same as Submitter	
A brief description of each crash test and its result:			

Required Test	Narrative	Evaluation
Number	Description	Results
3-70 (1100C)	Designated to evaluate the ability of a small vehicle to activate any breakaway, fracture, or yielding mechanism. Is considered optional for work zone traffic control weighting less than 220 lb (100 kg)	Non-Relevant Test, not conducted

	1	rage 3 01 3
Required Test	Narrative	Evaluation
Number	Description	Results
	5 di	<u> </u>
	For this test, Bone Safety work zone signs	
	were impacted. Two different vehicles were	
	used for the 3-71.	
	The first test article was aligned at 0° and	
	the second test article was aligned at 90° to	
	_	
	the impacting vehicle's direction of travel.	
	Per MASH, for devices weighing less than	
	220 pounds, Test 71 was conducted without	
	instrumentation for evaluating occupant	
	risk values OIV and RA per MASH test	
	description.	
	The first test artisle was impacted at 0° at a	
	The first test article was impacted at 0° at a	
	velocity of 63 mph (101.4 km/hr) by a 2014	
	Kia Rio 4 door sedan with a test inertia mass	
	of 2,458 lbs (1,115 kg). Upon impactthe roll	
	up sign released the sign stand and folded	
	over the front end of the vehicle. No	
	identifiable damage to the vehicle was	
	caused. Only surface cracks in the	
	windshield were identified, and all	
	evaluation criteria were met.	
	The second test vehicle, a 2016 Nissan Versa	
3-71 (1100)	with a mass of 2385 lb (1081.8 kg), impacted	
	the 90° sign stand at a speed of 62 mph (99.8	
	km/hr) . All evaluation criteria were met.	
	Impact points for both tests were within the	
	12" tolerance around the 1/4 point of	
	vehicles.	
	Neither test vehicle's occupant	
	•	
	compartment was penetrated by the test	
	articles. There was NO cab/passenger	
	compartment deformation in the 0 degree	
	test, and .4" (10.2 mm) deformation in the	
	foot well from the 90 degree test	
	Debris from the test articles did not block	
	the driver's vision after initial impact. The	
	vehicle remained upright and did not have	
	any roll and pitch throughout the test. The	
	vehicle did not leave its lane and its	
	trajectory was stable after both sign stands	
	were impacted.	
ı	TEST RESULT= PASS	
1		
	•	

For this test, two Bone Safety Signs Stands were impacted. The first test article was aligned at 0° and the second test article was aligned at 90° to the test vehicle's direction of travel. This test is intended to evaluate the sign 's behavior when impacted.

Per MASH, for devices weighing less than 220 pounds, Test 72 was conducted without instrumentation for evaluating occupant risk values OIV and RA per MASH test description.

The test was conducted using a commercially available 2009 Ram 1500 Pickup Truck with a test inertia mass of 5022 lbs (2,278 kg).

The test vehicle impacted the first sign stand (oriented at 0°) at a velocity of 61.8 mph (99.5 km/hr). Upon impact, the roll up sign released from the sign stand and folded over the front end of the vehicle. The top of the vertical cross frame detached and impacted the middle of the windshield causing surface cracks. The test vehicle continued along its path and impacted the second sign stand (oriented at 90°) at a velocity of 60.7 mph (97.7 km/hr). Upon impact, the roll up sign released from the Latch Bracket and folded over the front end of the vehicle. The top of the vertical cross frame impacted the bottom of the windshield. The test vehicle's occupant compartment was not penetrated by the test articles and there was NO inner cab/ passenger compartment deformation.

3-72 (2270P)

Impact points for both signs were within the 12" tolerance around the 1/4 point of vehicle, one toward passenger, the other toward driver.

Debris from the test article did not cause a hazard to the driver 's vision. The vehicle remained upright and did not have any roll and pitch throughout the test. The vehicle did not leave its lane and its trajectory was stable after both sign stands were impacted.

TEST RESULT = PASS

Full Scale Crash Testing was done in compliance with MASH by the following accredited crash test laboratory (cite the laboratory's accreditation status as noted in the crash test reports.):

Laboratory Name:	Calspan Corporation	
Laboratory Signature:		gitally signed by Mark J. Parisi te: 2021.04.02 13:14:25 -04'00'
Address:	4455 Genesee Street, Cheektowaga, NY 14225	Same as Submitter
Country:	USA	Same as Submitter
Accreditation Certificate Number and Dates of current Accreditation period :	L20-602 December 31, 2022	
Laboratory Name:	Calspan Corporation	

Submitter Signature: Ben F. Cohen Digitally signed by Ben F. Cohen Date: 2021.03.30 16:04:57 -04:00'

Submit Form

# **ATTACHMENTS**

#### Attach to this form:

- 1) Additional disclosures of related financial interest as indicated above.
- 2) A copy of the full test report, video, and a Test Data Summary Sheet for each test conducted in support of this request.
- 3) A drawing or drawings of the device(s) that conform to the Task Force-13 Drawing Specifications [Hardware Guide Drawing Standards]. For proprietary products, a single isometric line drawing is usually acceptable to illustrate the product, with detailed specifications, intended use, and contact information provided on the reverse. Additional drawings (not in TF-13 format) showing details that are relevant to understanding the dimensions and performance of the device should also be submitted to facilitate our review.

# FHWA Official Business Only:

Eligibility Letter		
Number	Date	Key Words